

Teste a snodo SA SAZPL25-S-DURBAL - SAZPL25-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sazpl25-s-durbal>


SAZPL25-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAZPL 25 S		25,40	34,93
			B
			C ₁
			d ₂
			69,85

type	inches	measurement [mm]		α	load rating	weight
		l ₁ min	h	[°]	C ₀ [kN]	[kg]
SAZP / SAZPL 25 S	1"	53,98	104,78	14	101,0	1,100

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496313
Diametro interno	25.4 mm
Diametro interno	1" inch
Diametro esterno	69.85 mm
Diametro esterno	2 3/4" inch
Spessore	34.93 mm
Spessore	1 3/8" inch
Tipo	SA
Peso	1100 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE