

## Teste a snodo SA SAZJ15-DURBAL - SAZJ15-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sazj15-durbal>

### SAZJ15



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

Description: DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size  $\geq 9$  with grease nipple can be mounted upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
rod end body pressed around inner ring

Lubrication:  
lubrication required



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAZJ 15		15,88	5/8 - 18	19,05	12,29	38,10

type	inches	measurement [mm]		alpha [°]	load rating C <sub>0</sub> [kN]	weight [kg]
		l <sub>1</sub> min	h			
SAZI / SAZIL 15	5 / 8 "	41,28	66,68	13,0	29,0	0,160

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496580
Diametro interno	15.88 mm
Diametro esterno	38.1 mm
Spessore	19.05 mm
Tipo	SA
Peso	160 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE