

Teste a snodo SA SAZJL15-DURBAL - SAZJL15-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sazjl15-durbal>

SAZJL15



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions in inch. Housing made of forged steel, sliding combination steel / steel. Size ≥ 9 with grease nipple can be mounted upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAZJL 15		15,88	5/8 - 18	19,05	12,29	38,10

type	inches	measurement [mm]		load rating	weight	
		l ₁ min	h	C ₀ [kN]	[g]	
SAZI / SAZJL 15	5 / 8 "	41,28	66,68	13,0	29,0	0,160

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496597
Diametro interno	15.88 mm
Diametro esterno	38.1 mm
Spessore	19.05 mm
Tipo	SA
Peso	160 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE