

## Teste a snodo SI DSIZJ6-DURBAL - DSIZJ6-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsizj6-durbal>

### DSIZJ6



**female thread:**  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches

**Description:** DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size: 9 with grease nipple can be mounted upon  
request.


**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
rod end body pressed around inner ring

**Lubrication:**  
lubrication required



order number	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>
DSIZJ 6	6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91

type	inches	h <sub>1</sub> min	W	h	α [°]	load rating C <sub>0</sub> (KN)	weight (kg)
DSIZJ / DSIZJL 6	1 / 4 "	15,88	9,53	33,32	13,5	9,6	0,023

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496726
Diametro interno	6.35 mm
Diametro esterno	19.05 mm
Spessore	9.53 mm
Tipo	SI
Peso	23 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE