

## Teste a snodo SI SIZJ9-DURBAL - DSIZJ9-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsizj9-durbal>


### SIZJ9



female thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4,  
series K,  
measurement in  
inches



Description: DIN ISO rod end K series. Dimensions  
in inch. Sliding combination steel / steel.  
Size: 9 with grease nipple can be mounted upon  
request.



Rod end body:  
surface zinc plated  
Sliding combination:  
steel / steel  
Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated  
Outer ring:  
rod end body pressed around inner ring  
Lubrication:  
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
	d	B	C <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>	
SIZJ 9	9,53	12,70	9,12	25,40	3/8 - 24	13,89	17,45	

type	inches	h <sub>1</sub> min	measurement [mm]		h	α	load rating	weight
			W			[°]	C <sub>0</sub> (kN)	[kg]
SIZJ / SIZJL 9	3 / 8"	19,05	14,27		41,28	11,0	16,0	0,059

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496795
Diametro interno	9.53 mm
Diametro esterno	25.4 mm
Spessore	12.7 mm
Tipo	SI
Peso	59 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE