

Teste a snodo SI SIZJ12-DURBAL - DSIZJ12-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsizj12-durbal>

SIZJ12



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required



order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJ 12	12,70	15,88	11,50	33,32	1/2 - 20	18,67	22,23

type	inches	h ₁ min	measurement [mm]	h	α [°]	load rating C ₀ [kN]	weight [kg]
SIZJ / SIZJL 12	1 / 2 "	25,40	19,05	53,98	10,0	28,0	0,132

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496870
Diametro interno	12.7 mm
Diametro esterno	33.32 mm
Spessore	15.88 mm
Tipo	SI
Peso	132 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE