


## Snodi sferici GE SI12-E-DURBAL - SI12-E-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/si12-e-durbal>

**SI12-E** 

**female thread; lubrication required, according to DIN ISO 12240-4; serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread	measurement (mm)						
d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>		
SI 12 E	M 12	10	8,0	34	17,5	22		

**measurement [mm]**

type	l <sub>3</sub> min	W	h	$\alpha$ [°]	load rating C <sub>0</sub> (kN)	weight (kg)
SI / SI12 E	23	19	50	11	24,5	0,096

### CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468000
Diametro interno	12 mm
Diametro esterno	34 mm
Spessore	10 mm
Tipo	GE
Peso	96 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE