

Teste a snodo SI SI30-ES-2RS-DURBAL - SI30-ES-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si30-es-2rs-durbal>

SI30-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.


rod end body:
surface zinc plated

Sliding combination:
steel / steel

inner ring:
bearing steel, hardened, ground and
phosphated

outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



| order number | | measurement [mm] | | | | | | |
|-------------------|------------------|------------------|----------|----|------|----|------|----|
| right hand thread | left hand thread | d | G | B | C1 | d2 | d3 | d4 |
| SI 30 ES (-2RS) | | 30 | M 30 x 2 | 22 | 19,0 | 73 | 40,0 | 50 |

| type | measurement [mm] | | | α [°] | load rating C_0 [kN] | weight [kg] |
|-----------------------|------------------|----|-----|-----------------|------------------------------|----------------|
| | l_2 min | W | h | | | |
| SI / SII 30 ES (-2RS) | 56 | 41 | 110 | 6 | 110,0 | 0,93 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952497228 |
| Diametro interno | 30 mm |
| Diametro esterno | 73 mm |
| Spessore | 22 mm |
| Tipo | SI |
| Peso | 930 g |
| Il filo | Filetto destro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE