

Teste a snodo SI SI50-ES-2RS-DURBAL - SI50-ES-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si50-es-2rs-durbal>

SI50-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DS1...ES-2RS with additional seals also available.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 50 ES (-2RS)		50	M 45 x 3	35	30,0	112	62,0	75

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_2 min	W	h			
SI / S1L 50 ES (-2RS)	68	65	160	6	290,0	3,5

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497549
Diametro interno	50 mm
Diametro esterno	112 mm
Spessore	35 mm
Tipo	SI
Peso	3500 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE