

Teste a snodo SI

SIL60-ES-2RS-DURBAL - DSIL60-ES-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil60-es-2rs-durbal>

SIL60-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSIL...ES-2RS with additional seals also available.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 60 ES (-2RS)		60	M 52 x 3

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SIL 60 ES (-2RS)	70	75	175	6	450,0	5,5

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497624
Diametro interno	60 mm
Diametro esterno	135 mm
Spessore	44 mm
Tipo	SI
Peso	5500 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE