

## Teste a snodo SI SIL60-ES-DURBAL - SIL60-ES-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/sil60-es-durbal>

### SIL60-ES



**female thread;**  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**order number**  
right hand thread    left hand thread  
**SIL 60 ES**

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SIL 60 ES	70	75	175	6	450,0	5,5

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497631
Diametro interno	60 mm
Diametro interno	2.362" inch
Diametro esterno	135 mm
Diametro esterno	5.315" inch
Spessore	44 mm
Spessore	1.732" inch
Tipo	SI
Peso	5500 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE