

## Teste a snodo SI SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si60-es-2rs-durbal>

### SI60-ES-2RS



female thread;  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
phosphated

Outer ring:  
bearing steel, hardened, ground and  
phosphated

Lubrication:  
lubrication required



| order number      |                  | measurement (mm) |          |    |      |     |      |    |
|-------------------|------------------|------------------|----------|----|------|-----|------|----|
| right hand thread | left hand thread | d                | G        | B  | C1   | d2  | d3   | d4 |
| SI 60 ES (-2RS)   |                  | 60               | M 52 x 3 | 44 | 38,0 | 135 | 70,0 | 88 |

| type                  | measurement [mm] |    |     |                 | load rating<br>$C_0$<br>[kN] | weight<br>[kg] |
|-----------------------|------------------|----|-----|-----------------|------------------------------|----------------|
|                       | $l_2$ min        | W  | h   | $\alpha$<br>[°] |                              |                |
| SI / SII 60 ES (-2RS) | 70               | 75 | 175 | 6               | 450,0                        | 5,5            |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | DURBAL        |
| N° Ean13         | 3663952497679 |
| Diametro interno | 60 mm         |
| Diametro esterno | 135 mm        |
| Spessore         | 44 mm         |
| Tipo             | -             |
| Peso             | 5500 g        |
| Il filo          | -             |
| Lubrificazione   | -             |
| Imballaggio      | -             |
| Standard         | -             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE