

Teste a snodo SI SI70-ES-DURBAL - SI70-ES-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si70-es-durbal>

SI70-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
d	G	B	C ₁	d ₂	d ₃	d ₄	98	
SI 70 ES		70	M 56 x 3	49	42,0	160	80,0	98

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SII 70 ES	80	85	200	6	610,0	8,6

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497747
Diametro interno	70 mm
Diametro interno	2.756" inch
Diametro esterno	160 mm
Diametro esterno	6.299" inch
Spessore	49 mm
Spessore	1.929" inch
Tipo	SI
Peso	8600 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE