

Teste a snodo SA SAL15-ES-DURBAL - SAL15-ES-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sal15-es-durbal>

SAL15-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| | SAL 15 ES | 15 | M 14 | 12 | 10,0 | 40 |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|----|---|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 15 ES | 34 | 20 | 63 | 8 | 8 | 36,0 | 0,140 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952498072 |
| Diametro interno | 15 mm |
| Diametro esterno | 40 mm |
| Spessore | 12 mm |
| Tipo | SA |
| Peso | 140 g |
| Il filo | Filetto sinistro |
| Lubrificazione | con |
| Imballaggio | - |
| Standard | Nessuno standard |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE