

Teste a snodo SA SA50-ES-DURBAL - SA50-ES-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sa50-es-durbal>

SA50-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SA 50 ES | | 50 | M 45 x 3 | 35 | 30,0 | 112 |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|-----|--|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 50 ES | 107 | 56 | 185 | | 6 | 290,0 | 3,400 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952498676 |
| Diametro interno | 50 mm |
| Diametro esterno | 112 mm |
| Spessore | 35 mm |
| Tipo | SA |
| Peso | 3400 g |
| Il filo | Filetto destro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE