


GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

GIHO-K-16DO



female thread;
hydraulic rod ends,
according to
DIN 24555

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE.. ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.



Sliding combination:
steel, lateral

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
polished

Lubrication:
lubrication required

order number		measurement [mm]								
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHO-K 16 D*		16	20,7	45	M 12 x 1,25	21	45	14	11	13

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 16 D	48	17	70,5	20	10	28,5	0,22

Marchio	DURBAL
N° Ean13	3663952500652
Diametro interno	16 mm
Diametro esterno	45 mm
Spessore	11 mm
Tipo	TAPR
Peso	220 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE