

## Teste a snodo TPN GK80-DO-DURBAL - GK80-DO-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/tpn/gk80-do-durbal>

### GK80-DO



**Description:** DIN ISO Hydraulic rod end with welding slope and dowel pin at the end of rod. Made of spherical plain bearing DGE... ES (ES-2RS) pressed into rod end housing. Sliding combination steel / steel.  
Type DGK...DO-2RS with two additional seals available on request with grease nipple.

hydraulic rod ends, according to DIN ISO 12240-4, series E



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication:

lubrication required

\* without grease nipple  
\*\* with grease nipple

order number	d	d <sub>1</sub>	d <sub>2</sub>	measurement [mm]			B	C <sub>1</sub>
GK 80 DO	80	89,4	180	6	95,0	55	47	

type	h <sub>1</sub>	h <sub>2</sub>	measurement [mm]		D	d <sub>1</sub>	α	load rating	weight
			l <sub>1</sub>	l <sub>2</sub>			[°]	C <sub>0</sub> [kN]	[kg]
GK 80 DO	141	231,0	98,0	5,0	120	105,0	6	620,0	8,700

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952501536
Diametro interno	80 mm
Diametro esterno	180 mm
Spessore	55 mm
Tipo	TPN
Peso	8700 g
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE