

Snodi sferici GEG GE35-LO-DURBAL - GE35-LO-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/geg/ge35-lo-durbal>

GE35-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring:
bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication:
lubrication required

| order number | measurement [mm] | | | | |
|--------------|------------------|----|----|--------------------|----|
| GE 35 LO | d | B | C | d ₁ min | D |
| | 35 | 35 | 20 | 40,0 | 55 |

| type | measurement [mm] | | d ₁ | r ₁ | load rating C ₁₀ [N] | weight [kg] |
|----------|---------------------|---------------------|----------------|----------------|---------------------------------------|----------------|
| | r ₁₅ min | r ₂₅ min | | | | |
| GE 35 LO | 0,6 | 1,0 | 48,0 | 4 | 399 | 0,253 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952506463 |
| Diametro interno | 35 mm |
| Diametro esterno | 55 mm |
| Spessore | 20 mm |
| Tipo | GEG |
| Peso | 253 g |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE