

Teste a snodo SA BRTM16-03-501-DURBAL - BRTM16-03-501-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/brtm16-03-501-durbal>

BRTM16-03-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number			measurements [mm]						
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	b ₁	b ₂	b ₃
BRTM 16 -03	-501		16	M 16	19,0	42	21		15
measurements [mm]			weight		rotational speed limit		basic load rating		stat.
type	h	l	b ₃	α [°]	[kg]	n _{max} [rpm]	C [N]	C ₁₀ [N]	
BRTM 16	66	40	22	7,0	0,185	975	13300	8900	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952506753
Diametro interno	16 mm
Diametro esterno	42 mm
Spessore	21 mm
Tipo	SA
Peso	185 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE