

## Teste a snodo SA BRTM25-00-502-DURBAL - BRTM25-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/brtm25-00-502-durbal>

### BRTM25-00-502



**male thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**liner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminum-complex soap grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]									
type	type	type	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	
BRTM 25 -00	-502		25	M 24 x 2		29,5	64		31		22
measurements [mm]		weight	rotational speed limit	basic load rating							
type	h	l	b <sub>3</sub>	α	[°]	[kg]	n <sub>max</sub>	C	d <sub>m</sub>	stat.	C <sub>10</sub>
BRTM 25	94	57	30	5,0		0,596	600	24900			18500

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952506784
Diametro interno	25 mm
Diametro esterno	64 mm
Spessore	31 mm
Tipo	SA
Peso	596 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE