

## Teste a snodo SA BRTM30-00-502-DURBAL - BRTM30-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/brtm30-00-502-durbal>

### BRTM30-00-502



**male thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**liner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminum-complex soap grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]								
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	
BRTM 30 -00	-502		30	M 30 x 2		34,5	70		37	25
measurements [mm]		weight	rotational speed limit	basic load rating						
type	h	l	b <sub>3</sub>	α [°]	weight [kg]	rotational speed limit n <sub>max</sub> [rpm]	basic load rating d <sub>m</sub> [N]	stat. C <sub>0</sub> [N]	stat. C <sub>10</sub> [N]	
BRTM 30	110	66	35	7,5	0,912	450	32500		24850	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952506814
Diametro interno	30 mm
Diametro esterno	70 mm
Spessore	37 mm
Tipo	SA
Peso	912 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE