

Teste a snodo SI PF10-00-501-DURBAL - PF10-00-501-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/pf10-00-501-durbal>

PF10-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread:
long-term lubrication, low maintenance, shields

order number		measurements [mm]													
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃				
PF 10-00-501			10	15	M 8	13,0	30	13,0			9				
measurements [mm]			weight		calculation factors		rotational speed limit		basic load rating		stat.				
type	h	l	l ₁	l ₂	r	SW	α	[°]	[kg]	Y	%	n _{max} [rpm]	C [N]	C ₀ [N]	C ₁₀ [N]
PF 10	38	17	14,5	10	13	7,0	0,063		1,90	1,81		1225	2605		985

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507361
Diametro interno	10 mm
Diametro esterno	30 mm
Spessore	13 mm
Tipo	SI
Peso	63 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE