

Teste a snodo SI PF10-00-502-DURBAL - PF10-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/pf10-00-502-durbal>

PF10-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread;
long-term lubrication, low maintenance, shields



order number		measurements [mm]													
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃				
PF 10 -00	-502		10	15	M 8	13,0	30	13,0			9				
		measurements [mm]													
type	h	l	l ₁	l ₂	l ₃	r	SW	α	α ₁	weight [kg]	calculation factors Y	%	rotational speed limit P _{max} [min ⁻¹]	basic load rating dyn. C [N]	stat. C ₀ [N]
PF 10	38	17	14,5	10	13	7,0				0,063	1,90	1,81	1225	2605	985

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507378
Diametro interno	10 mm
Diametro esterno	30 mm
Spessore	13 mm
Tipo	SI
Peso	63 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE