

Teste a snodo SA PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm05-01-502-durbal>

PM05-01-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]					measurements [mm]					weight			rotational speed limit			basic load rating	
type	type	type	type	type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y _c	n _{max} [min ⁻¹]	C	C ₀
PM 05 -01	-502	S	M	8 x 1		7,5			19	12	12	12	12	8			1350	1610	480
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	weight [kg]	calculation factors	rotational speed limit	basic load rating	dyn. rating	stat. rating				
PM 05	16	13	33,5	1,5	2,5	7,0			0,033	1,51	1,58	1350	1610	480					

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507446
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	12 mm
Tipo	SA
Peso	33 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE