


Teste a snodo SA

PM05-01-501-DURBAL - PM05-01-501-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm05-01-501-durbal>

PM05-01-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]					measurements [mm]				weight		rotational speed limit		basic load rating	
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	Y ₀	n _{max} [min ⁻¹]	C	C ₀	B
PM 05 -01	-501	S	M	8 x 1	7,5	19	12	12	12	8						
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]		rotational speed limit [min ⁻¹]		basic load rating [N]		rating [N]	
PM 05	16	13	33,5	1,5	2,5	7,0	0,033	1,51	1,58	1350	1610	480				

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507453
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	12 mm
Tipo	SA
Peso	33 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE