

Teste a snodo SA PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm08-02-502-durbal>

PM08-02-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



| order number | | measurements [mm] | | | weight | | | rotational speed limit | | | basic load rating | | |
|-------------------|------|-------------------|------------|------------------------|--------|-------------------|-------|------------------------|-------------|------|-------------------|-----|------|
| type | type | d1 | d2 | d3 | d4 | d5 | d7 | b1 | b2 | b3 | Y | C | C0 |
| PM 08-02 | -502 | 8 | M 12 x 1.5 | 11,0 | 30 | 17 | 15 | 10 | | | | | |
| measurements [mm] | | weight | | rotational speed limit | | basic load rating | | | | | | | |
| type | l1 | l2 | l3 | h1 | h2 | u | z | alpha | alpha prime | Y | C | C0 | beta |
| PM 08 23 | 20 | 48,5 | | 2,0 | 2,5 | 8,5 | 0,088 | 1,9 | 1,81 | 1225 | 2605 | 985 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952507521 |
| Diametro interno | 8 mm |
| Diametro esterno | 30 mm |
| Spessore | 15 mm |
| Tipo | SA |
| Peso | 88 g |
| Il filo | Filetto sinistro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE