

Teste a snodo SA

PM10-00-501-DURBAL - PM10-00-501-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm10-00-501-durbal>

PM10-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating					
type	sp. thread	d1	d2	d4	d5	d7	b1	b2	b3	Y	Yc	C	C0		
PM 10 -00	-501	10	M 14 x 1,5	13,5	36	19	20	14							
measurements [mm]		weight		rotational speed limit		basic load rating									
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	[kg]	Y	Yc	rmax [mm]	C [N]	C0 [N]
PM 10	49,5	28	82	2,5	2,5	9,5	0,168	1,69	1,77	1100	5120	1905			

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507545
Diametro interno	10 mm
Diametro esterno	36 mm
Spessore	20 mm
Tipo	SA
Peso	168 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE