

Teste a snodo SA

PM12-02-502-DURBAL - PM12-02-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm12-02-502-durbal>

PM12-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]					measurements [mm]					weight		rotational speed limit		basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	stat.	stat.
PM 12 -02	-502	12	M 16 x 1,5	15,0	40	21	20	14					1,81	1,90	1050	5345	2065

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507606
Diametro interno	12 mm
Diametro esterno	40 mm
Spessore	20 mm
Tipo	SA
Peso	204 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE