

## Teste a snodo SA

### PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm17-00-502-durbal>

#### PM17-00-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USGA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]			weight		calculation factors		rotational speed limit		basic load rating	
type	sp/ha/ct/mad	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16				
measurements [mm]												
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	weight [kg]	Y	Yc
PM 17	62,5	36	105	3,5	2,5	7,0	0,401	2,35	2,46	875	5575	2680

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507675
Diametro interno	17 mm
Diametro esterno	48 mm
Spessore	22 mm
Tipo	SA
Peso	401 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE