

Teste a snodo SA PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]			measurements [mm]			measurements [mm]								
type	type	type	type	type	type	type	type	type	type	type						
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16								
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		stat.						
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	α' [°]	weight [kg]	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	stat. [N]
PM 17	62,5	36	105	3,5	2,5	7,0	0,401			0,401	2,35	2,46	875	5575	2680	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507675
Diametro interno	17 mm
Diametro esterno	48 mm
Spessore	22 mm
Tipo	SA
Peso	401 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE