

Teste a snodo SA PM20-02-502-DURBAL - PM20-02-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pm20-02-502-durbal>

PM20-02-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	weight	calculation factors	Y	Yc	nmax [min ⁻¹]	C [N]	C0 [N]
PM 20 -02	-502	20	M 24 x 1,5	24,0	56	30	24	18								
type	l1	l2	l3	h1	h2	u	z	alpha [°]	[kg]							
PM 20	41	41	89,5	3,5	3,0	5,5			0,519		2,76	2,90		775	6165	3140

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507729
Diametro interno	20 mm
Diametro interno	0.787" inch
Diametro esterno	56 mm
Diametro esterno	2.205" inch
Spessore	24 mm
Spessore	0.945" inch
Tipo	SA
Peso	519 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE