

Teste a snodo SI

BEF22-20-501-DURBAL - BEF22-20-501-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/bef22-20-501-durbal>

BEF22-20-501



rod end housing:
forged steel, tempered, surface galvanized, free of Cr VI


joint ball:
ball bearing steel, hardened and ground, surface superfinished and chromium plated

race:
nylon / teflon / glass fibre compound

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral spherical plain bearing

female thread:
maintenance free, adapter sizes according to DIN ISO 12240-4, series K, thread according to ISO 8139



order number		measurements [mm]									
type	specification	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	b ₁	b ₂
BEF 22	-20 -501	22	30,0	M 22 x 1,5	54	38	38,05	28	20,0		
measurements [mm]		weight		basic load rating							
type	h	l	l ₁	l ₂	SW	α ₁ ¹ [°]	α ₂ ² [°]	[kg]	dyn. C [N]	stat. C ₀ [N]	
BEF 22	84	37	12,0	26	32	15,5	10,0	0,520	38230	95600	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952508238
Diametro interno	22 mm
Diametro esterno	54 mm
Spessore	28 mm
Tipo	SI
Peso	520 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE