

Teste a snodo SI

BEF25-60-502-DURBAL - BEF25-60-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/bef25-60-502-durbal>

BEF25-60-502



rod end heading:
stainless steel 1.4301, rolled thread,
surface with pickling treatment


joint ball:
stainless steel, hardened and ground,
surface superfinished

race:
nylon / teflon / glass fibre compound

tolerances:
see page 10

**DURBAL® heavy-duty rod ends
with integral spherical
plain bearing in stainless steel**

female thread:
maintenance free,
adapter sizes
according to
DIN ISO 12240-4,
series K,
thread according to
ISO 8139



order number		measurements [mm]										
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	b ₁	b ₂
BEF 25	-60	-502	25	33,5	M 24 x 2	60	42	42,80	31	22,0		
		measurements [mm]										
type	h	l	l ₁	l ₂	SW	α ₁ [°]	α ₂ [°]	β [°]	weight	basic load rating		
BEF 25	94	42	12,0	30	36	15,0	10,0		0,705	27860	79100	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952509617
Diametro interno	25 mm
Diametro esterno	60 mm
Spessore	31 mm
Tipo	SI
Peso	705 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE