


Snodi sferici GE


BRTM5-8-00-502-DURBAL - BRTM5-8-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/brtm5-8-00-502-durbal>

BRTM5/8-00-502 

male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [inches]								
type	right hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRTM 5/8 -00	-502	.625	.6250-18 UNF	.748	1.653	.826	.590			
measurements [inches]		weight		rotational speed limit		basic load rating				
type	h	l	l ₂	α	α'	rpm	C	C ₀	C ₁₀	C ₅₀
BRTM 5/8	2.618	1.574	.944	7,0	0,182	975	13300	8900		

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468307
Diametro interno	15.88 mm
Diametro esterno	41.99 mm
Spessore	20.98 mm
Tipo	GE
Peso	182 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE