

Teste a snodo SA BRTM1-1-00-502-DURBAL - BRTM1-1-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/brtm1-1-00-502-durbal>

BRTM1/1-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [inches]						
type	right hand thread	left hand thread	d ₁	d ₂ class 2	d ₄	d ₅	b ₁	b ₂
BRTM 1/1 -00		-502	1.000	1.0000-12 UNF	1.161	2.519	1.220	.866
		measurements [inches]						
type	h	l	b ₂	α [°]	weight [kg]	rotational speed limit C [min ⁻¹]	basic load rating dyn. C _d [N]	stat. C _s [N]
BRTM 1/1	3.720	2.264	1.279	5,0	0.590	600	24900	18500

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952509952
Diametro interno	25.4 mm
Diametro esterno	63.98 mm
Spessore	30.99 mm
Tipo	SA
Peso	590 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE