


Teste a snodo SI BRF5-8-00-502-DURBAL - BRF5-8-00-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/brf5-8-00-502-durbal>

BRF5/8-00-502 

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminum complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1 1/4)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]										
type	right hand thread / left hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	b3	
BRF 5/8 -00	-502	.625	.866	.6250-18 UNF	.744	1.653	1.062	.826	.590			
measurements [inches]		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	l1	l2	SW	α [°]	weight [kg]	Y	%	rpm	C [N]	C0 [N]
BRF 5/8	2.539	1.102	.322	.885	.866	8.0	0.220	2.24	2.35	975	6250	2350

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510163
Diametro interno	15.88 mm
Diametro interno	5/8" inch
Diametro esterno	41.99 mm
Diametro esterno	1.653" inch
Spessore	20.98 mm
Spessore	0.826" inch
Tipo	SI
Peso	220 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE