

## Teste a snodo SI

### BEF5-8-20-502-DURBAL - BEF5-8-20-502-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/bef5-8-20-502-durbal>

#### BEF5/8-20-502



**rod end housing:**  
forged steel, tempered, surface galvanized, free of Cr-VI


**joint ball:**  
ball bearing steel, hardened and ground, surface superfinished and chromium plated

**race:**  
nylon / teflon / glass fibre compound

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral spherical plain bearing**

**female thread:**  
maintenance free, dimensions in inches



order number		measurements [inches]										
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	d <sub>8</sub>	b <sub>1</sub>	b <sub>2</sub>
BEF 5/8 -20		-502	.625	.866	.6250-18 UNF	1.654	1.063	1.125	.826	.590		
		measurements [inches]										
type	h	l	l <sub>1</sub>	l <sub>2</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating C <sub>0</sub> [N]	stat. C <sub>0</sub> [N]		
BEF 5/8	2.539	1.102	.350	.885	.866	15.5	8.5	0.231	22410	69600		

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510583
Diametro interno	15.88 mm
Diametro esterno	42.01 mm
Spessore	20.98 mm
Tipo	SI
Peso	231 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE