




Gusci a rullini TJ7215-RBC - TJ7215-RBC

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/tj7215-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fit	Housing Shoulder Dia	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Min.	Max.	+000 -000	Max	+/- 1.984"		
TJ 7215	1 1/8	1.1259	1.1268	1.6250	1.6245	1.250	.040	1.318	10,600	20,400

Limit Speed (rpm)	Recommended Shaft Diameter				Recommended Housing Bore				BEARING PART NUMBER 1)		
	ISO H6 use with H7 sig fit	ISO H6 use with H7 sig fit		ISO H7 use with H7 sig fit	Slip Fit ISO H7		Press Fit ISO N7				
	Max.	Min.	Max.	Min.	Min.	Max.	Mean Fit	Min.	Max.	Mean Fit	
10,500	1.1290	1.1245	1.1242	1.1237	1.6250	1.6280	.0007L	1.6237	1.6247	.0006T	TJ 7215

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

CARATTERISTICHE DEL PRODOTTO

Marchio	RBC
N° Ean13	3663952533506
Diametro interno	28.575 mm
Diametro esterno	41.275 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE