

Cuscinetti a sfera fila unica 1602-SS-NICE - 1602-SS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1602-ss-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|-----------------------------|---|-------------------------------|------------------------------------|------------------------------------|--------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.00 -0.0005 -0.013 | +0.000 +0.00 -0.0005 -0.013 |
| 1602™ | | | | | SS | 0.2500 6.350 | 0.6875 17.463 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ⁰ (oz) (g) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.2500 6.350 | 511 2274 | 170 757 | 0.02 0.01 | 0.330 8.38 | 0.614 15.60 | 0.012 0.30 | |

⁰ Width for sealed versions = 0.3125 (7.938) ¹ Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952556956 |
| Diametro interno | 6.35 mm |
| Diametro esterno | 17.463 mm |
| Spessore | 6.35 mm |
| Peso | 10 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE