


Cuscinetti a sfera fila unica 1616-SS-NICE - 1616-SS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1616-ss-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|--|---|--|-------------------------------------|--|--|---|---|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| 1616™ | | | | SS | | 0.5000 12.700 | 1.1250 28.575 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C₀ (lb) (N) | W⁰ (lb) (g) | d_a min (in) (mm) | D_a max (in) (mm) | r max (in) (mm) | |
| +0.000 +0.000 -0.005 -0.13 | 1200 5340 | 475 2114 | 0.06 0.03 | 0.622 15.80 | 1.014 25.76 | 0.025 0.64 | |

Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952557335 |
| Diametro interno | 12.7 mm |
| Diametro esterno | 28.575 mm |
| Spessore | 9.525 mm |
| Peso | 30 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE