


Cuscinetti a sfera fila unica 1623-SC-NICE - 1623-SC-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1623-sc-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|------------------------------|------------------------------------------|------------------------|------------------------------------|------------------------------------|--------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.005 -0.013 | +0.000 +0.000 -0.005 -0.013 |
| 1623™ | | SC | | | | 0.6250 15.875 | 1.2750 34.925 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lbf) (N) | STATIC C ₀ (lbf) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.4375 11.113 | 1878 8367 | 850 3783 | 0.10 0.05 | 0.753 19.13 | 1.203 30.56 | 0.025 0.64 | |

Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952557489 |
| Diametro interno | 15.875 mm |
| Diametro interno | 5/8" inch |
| Diametro esterno | 34.925 mm |
| Diametro esterno | 1 3/8" inch |
| Spessore | 11.113 mm |
| Spessore | 7/16" inch |
| Peso | 50 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE