


Cuscinetti a sfera fila unica 1640-NS-NICE - 1640-NS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1640-ns-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | | |
|----------------------------|-----------------------------|--------------------|---|------------------------|------------------------------------|--|---------------------------------------|------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) | |
| 1640™ | | | | | | -0.0000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 | 22.225 50.800 |
| WIDTH B (in) (mm) | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| | DYNAMIC C (lb) (N) | | STATIC C ₀ (lb) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.5625 14.288 | 2967 13203 | | 1350 6008 | 0.29 0.13 | 1.113 28.27 | 1.780 44.70 | 0.035 0.89 | |

Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952557755 |
| Diametro interno | 22.225 mm |
| Diametro esterno | 50.8 mm |
| Spessore | 14.288 mm |
| Peso | 130 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE