


Cuscinetti a sfera fila unica 1657-DS-NICE - 1657-DS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1657-ds-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|-----------------------------|--------------------|-----------------------------------------|------------------------|------------------------------------|---------------------------------------|----------------------------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 1657™ | | | DS | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 2.925 65.088 |
| WIDTH B (in) (mm) | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
| | DYNAMIC C (lb) (N) | | STATIC C ₀ (lb) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.6875 17.463 | 5380 23852 | | 2620 11669 | 0.51 0.23 | 1.500 38.10 | 2.314 58.78 | 0.035 0.89 |

Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952557977 |
| Diametro interno | 31.75 mm |
| Diametro esterno | 65.088 mm |
| Spessore | 17.463 mm |
| Peso | 230 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE