




Cuscinetti a sfera fila unica 3004-SC-NICE - 3004-SC-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3004-sc-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3004™		SC				+0.005 +0.13 -0.000 -0.05 9.525	+0.000 +0.00 -0.0005 ⓐ -0.015 0.8750 22.225

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2813 ⓑ 7.1450	325 1448	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38

ⓐ Width for sealed versions = 0.3438 (8.733) ⓑ Weights given are for greased and sealed versions
 ⓒ 3038 and larger +0.0005/-0.005 (-0.001/-0.15)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558134
Diametro interno	9.525 mm
Diametro esterno	22.225 mm
Spessore	7.145 mm
Peso	10 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE