

Cuscinetti a sfera fila unica
3007-SC-NICE - 3007-SC-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3007-sc-nice>

3000 Series® Semi-Ground Radial Bearings

- PRECISION GRINDING ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



TO CLEAR



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3007™			SC			+0.005 +0.13 -0.000 -0.013	+0.000 +0.50 -0.005 -0.013

BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	350 1568	300 1335	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38

Ⓜ Weights given are for greased and sealed versions
Ⓜ 3008 and larger +0.000/-0.006 (+/-0.002/-0.15)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558264
Diametro interno	11.113 mm
Diametro esterno	23.02 mm
Spessore	7.938 mm
Peso	10 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE