

Cuscinetti a sfera fila unica 3023-DS-NICE - 3023-DS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3023-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3023™ | | | | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.0005 -0.013 |
| | | | | | | 0.6250 15.875 | 1.3750 34.925 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|-----------------------------|--------------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC Ca (lb) (N) | W ^⓪ (lb) (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.4375 11.113 | 940 4183 | 860 3783 | 0.10 0.05 | 0.753 19.13 | 1.203 30.56 | 0.025 0.64 |

^⓪ Weights given are for greased and sealed versions
^⓪ 3023 and larger +0.0005/-0.005 (-0.002/-0.13)

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952558578 |
| Diametro interno | 15.875 mm |
| Diametro esterno | 34.925 mm |
| Spessore | 11.113 mm |
| Peso | 50 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE