

Cuscinetti a sfera fila unica 3030-SC-NICE - 3030-SC-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3030-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	
3030™	SC					
					BORE	O.D.
					d	D
					(in)	(in)
					(mm)	(mm)
					+0.005	+0.000
					+0.13	+0.00
					-0.000	-0.0005
					-0.00	-0.013
					0.7500	1.5050
					19.050	41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH	DYNAMIC	STATIC	W	d _a min	D _a max	r max
B	C	C ₀	W	d _a min	D _a max	r max
(in)	(lb)	(lb)	(kg)	(in)	(in)	(in)
(mm)	(N)	(N)	(kg)	(mm)	(mm)	(mm)
0.5000	1300	1010	0.16	0.965	1.446	0.025
12.700	5785	4485	0.07	24.51	36.73	0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.0005/-0.005 (+0.001/-0.13)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558660
Diametro interno	19.05 mm
Diametro esterno	41.275 mm
Spessore	12.7 mm
Peso	70 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE