

## Cuscinetti a sfera fila unica 3038-SS-NICE - 3038-SS-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3038-ss-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX  |             |             |               |               | PRINCIPLE DIMENSIONS |                                    |                                      |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN                 | BORE<br>d<br>(in)<br>(mm)          | O.D.<br>D<br>(in)<br>(mm)            |
| 3038™   |             |             |               | SS            |                      | +0.005<br>+0.13<br>-0.000<br>-0.00 | +0.000<br>+0.00<br>-0.0005<br>-0.013 |
|         |             |             |               |               |                      | 0.7500<br>19.050                   | 2.0000<br>50.800                     |

| BASIC LOAD RATINGS         |                             |                             | WEIGHT                         | ABUTMENT AND FILLET DIMENSIONS     |                                    |                       |
|----------------------------|-----------------------------|-----------------------------|--------------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH<br>B<br>(in)<br>(mm) | DYNAMIC<br>C<br>(lb)<br>(N) | STATIC<br>Co<br>(lb)<br>(N) | W <sup>⓪</sup><br>(lb)<br>(kg) | d <sub>a</sub> min<br>(in)<br>(mm) | D <sub>a</sub> max<br>(in)<br>(mm) | r max<br>(in)<br>(mm) |
| 0.9625<br>14.288           | 1480<br>6588                | 1350<br>6008                | 0.32<br>0.15                   | 0.988<br>25.10                     | 1.760<br>44.70                     | 0.035<br>0.89         |

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3038 and larger +0.0005/-0.0005 (+0.001/-0.12)

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | NICE          |
| N° Ean13         | 3663952558813 |
| Diametro interno | 19.05 mm      |
| Diametro esterno | 50.8 mm       |
| Spessore         | 14.288 mm     |
| Peso             | 150 g         |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE