




Cuscinetti a sfera fila unica 7508-DL-NICE - 7508-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/7508-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings 

- PRECISION GRINDING ON ALL CONTACT SURFACES - GRINDING FINISH TO THE 1000 RMSH STANDARD
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAXIMUM SPEED RANGE - HIGH RPM
- TRIPLEX HARDENED BEARING STEEL
- REFINED FINISH
- WIDE RETAINING STAIRS
- DOUBLE BEADED STAIRS
- INTERNAL OPERATIVE RINGS - IN CONTACT WITH THE BALLS
- AVAILABLE IN BOTH BEADED OR OPEN
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO BE ORDERED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHAFT AND HOUSING

| BEARING | PRINCIPLE DIMENSIONS | | | | |
|---------|----------------------------|----------------------------|----------------------------|----------------------------------|----------------------------|
| | BORE d (in) (mm) | O.D. D (in) (mm) | WIDTH B (in) (mm) | INNER WIDTH C (in) (mm) | F (in) (mm) |
| 7508™ | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 |
| | 0.000 12.70 | 1.7920 44.45 | 0.6250 15.88 | 0.0625 1.58 | 0.7500 19.05 |

| PRINCIPLE DIMENSIONS | | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
|----------------------|-------------------|-------------------|--------------------|-----------------------------|---|--------------------------------|------------------------|------------------------|-----------------------|
| G (in) (mm) | H (in) (mm) | J (in) (mm) | R (in) (mm) | Dynamic C (lb) (N) | Static C ₀ (lb) (N) | W ⊕ (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.136 3.45 | 0.042 1.07 | 1.9219 48.82 | 0.035 0.89 | 8595 11548 | 1025 4581 | 0.33 0.15 | 0.750 19.05 | 1.500 38.10 | 0.036 0.89 |

⊕ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ⊕ Tolerance for 7514™ and larger is +0.000/-0.005 (+.000/-0.015)
 ⊕ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ⊕ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3616060473271 |
| Diametro interno | 12.7 mm |
| Diametro esterno | 44.45 mm |
| Spessore | 15.88 mm |
| Peso | 150 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE