



Cuscinetti a sfera fila unica 7514-DL-NICE - 7514-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/7514-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings 

- PRECISION GRINDING ON ALL CONTACT SURFACES - GRINDING TO THE 100 MICRA RANGE
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000 - 10000 RPM
- THROUGH HARDENED BEARING STEEL
- REFINED FINISH
- WIDE RETAINING STAIRS
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE CONTACT ROLL WITH TIGHT SLEEVES
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS MEET A FULL ISO 9001 CERTIFIED QUALITY MANAGEMENT SYSTEM
- RECOMMENDED FOR APPLICATIONS WHERE DURABILITY, STABILITY AND PRECISION ARE ESSENTIAL



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7514	+0.000 -0.005 -0.013	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	0.025 1.59	7500 19.05	1.306 33.17

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	A (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W ⊕ (in) (mm)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.138 3.45	0.042 1.07	2.1563 54.77	0.035 0.89	9970 13217	1950 6008	0.36 0.16	1.125 28.58	1.750 44.45	0.036 0.89

⊕ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
⊕ Tolerance for 7514™ and larger is +0.000/-0.005 (+.000/-0.015)
⊕ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
⊕ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473301
Diametro interno	22.23 mm
Diametro esterno	50.8 mm
Spessore	15.88 mm
Peso	160 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE